

This industrial-duty, rechargeable lantern features a bright 615 lumens of light in a smooth flood pattern.



6 LEDs wide pattern parabolic reflectors produce a smooth flood pattern; optimized electronics provide regulated intensity

Two levels of lighting:

- High: 615 lumens; 126m beam distance; runs 8 hours
- Low: 330 lumens; 93m beam distance; runs 18 hours

**Standard System** – International safety orange or high visibility yellow: includes shoulder strap; includes AC and DC chargers and mounting rack; ideal for field maintenance, inspection of construction sites and remote equipment.

**Vehicle Mount System** – International safety orange or high visibility yellow: comes with vehicle-mountable hard-wire rack and shoulder strap.

**Power Failure System** – International safety orange: includes AC and DC chargers and “smart” power failure circuitry automatically illuminates when the E-Flood LiteBox when the power goes off.

IPX4 rated for water-resistance

11.5 in. (29.21 cm); 7 lbs (3583.38g)

Rack meets requirements of NFPA 1901-14.1.11.2 (2016) mounted in any position

Limited Lifetime Warranty

Visit [streamlight.com](http://streamlight.com) for full warranty information

- #45801 - E-Flood LiteBox with 120V AC/12V DC - Orange
- #45822 - E-Flood LiteBox with 230V AC/12V DC - Orange
- #45803 - E-Flood LiteBox with 240V AC/12V DC - Orange
- #45801 - E-Flood LiteBox with 120V AC/12V DC - Yellow
- #45822 - E-Flood LiteBox with 230V AC/12V DC - Yellow
- #45823 - E-Flood LiteBox with 240V AC/12V DC - Yellow
- #45805 - E-Flood LiteBox Vehicle Mount - Orange
- #45825 - E-Flood LiteBox Vehicle Mount - Yellow
- #45807 - E-Flood LiteBox Power Failure with 120V AC/12V DC - Orange
- #45808 - E-Flood LiteBox Power Failure with 230V AC/12V DC - Orange
- #45806 - E-Flood LiteBox (without charger) - Orange
- #45826 - E-Flood LiteBox (without charger) - Yellow