

1. Identification

Product identifier	LPS® CFC Free Nu
Other means of identification	
Part Number	05416
Recommended use	A spray cleaner designed to remove dirt, moisture, dust, flux or oxides from the internal components of electronic or precision equipment such as circuit boards.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer	
Company name	ITW Pro Brands
Address	4647 Hugh Howell Rd. Tucker, GA 30084
Country	(U.S.A.) Tel: +1 770-243-8800
In Case of Emergency	1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.)
Website	www.itwprobrands.com
E-mail	lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure (inhalation)	Category 2 (nervous system)
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Suspected of damaging fertility. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Avoid breathing vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	84.16, 81.79% of the mixture consists of component(s) of unknown acute oral toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Methylpentane		107-83-5	50 - 60
1, 1 Difluoroethane		75-37-6	20 - 30
Isopropanol		67-63-0	5 - 10
Pentane		109-66-0	5 - 10
N-hexane		110-54-3	<1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness or dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Isopropanol (CAS 67-63-0)	PEL	980 mg/m ³
		400 ppm
N-hexane (CAS 110-54-3)	PEL	1800 mg/m ³
		500 ppm
Pentane (CAS 109-66-0)	PEL	2950 mg/m ³
		1000 ppm

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value
Isopropanol (CAS 67-63-0)	PEL	980 mg/m ³
		400 ppm

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value
	STEL	1225 mg/m ³ 500 ppm
N-hexane (CAS 110-54-3)	PEL	180 mg/m ³ 50 ppm
Pentane (CAS 109-66-0)	PEL	1800 mg/m ³ 600 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-hexane (CAS 110-54-3)	TWA	50 ppm
Pentane (CAS 109-66-0)	TWA	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m ³ 500 ppm
	TWA	980 mg/m ³ 400 ppm
N-hexane (CAS 110-54-3)	TWA	180 mg/m ³ 50 ppm
Pentane (CAS 109-66-0)	Ceiling	1800 mg/m ³ 610 ppm
	TWA	350 mg/m ³ 120 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1, 1 Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m ³ 1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
N-hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

N-hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

N-hexane (CAS 110-54-3) Danger of cutaneous absorption

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol. Liquefied gas.
Color	Clear colorless or nearly colorless.
Odor	Mild.
Odor threshold	Not established
pH	Not available.
Melting point/freezing point	-198.4 °F (-128 °C) estimated
Initial boiling point and boiling range	140.9 °F (60.5 °C) Dispensed liquid
Flash point	< 1.4 °F (< -17.0 °C) Tag Closed Cup Dispensed liquid
Evaporation rate	< 1 BuAc (Ethyl Ether= 1)
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 %
Flammability limit - upper (%)	7 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	352.53 mm Hg @ 38°C
Vapor density	> 1 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 10 % by weight
Partition coefficient (n-octanol/water)	Not established
Auto-ignition temperature	582.8 °F (306 °C)
Decomposition temperature	Not Established
Viscosity	< 3 cSt @ 25°C
Other information	
Explosive properties	Not explosive.
Heat of combustion	> 30 kJ/g
Oxidizing properties	Not oxidizing.

Percent volatile	100 %
Specific gravity	0.8 - 0.82 @ 20°C
VOC	74 % per State & Federal Consumer Product Regulations; 600 g/L per SCAQMD Rule 102

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Chlorine. Isocyanates.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness or dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness or dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test Results
1, 1 Difluoroethane (CAS 75-37-6)		
Acute		
Inhalation		
Gas		
LC50	Rat	> 440000 ppm, 4 Hours
Isopropanol (CAS 67-63-0)		
Acute		
Inhalation		
LC50	-	51 mg/l, 8 Hours
Oral		
LD50	Rat	4.7 g/kg
N-hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
Inhalation		
Vapor		
LC50	Rat	> 32 mg/l, 4 Hours
Oral		
LD50	Rat	29000 mg/kg
Pentane (CAS 109-66-0)		
Acute		
Inhalation		
Vapor		
LC50	Rat	> 25 mg/l, 4 Hours

Components	Species	Test Results
Oral LD50	Rat	> 2000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens		
Isopropanol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.	
Further information	Symptoms may be delayed.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) > 1400 mg/l, 96 hours
N-hexane (CAS 110-54-3)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1, 1 Difluoroethane	0.75
2-Methylpentane	3.21
Isopropanol	0.05
N-hexane	3.9
Pentane	3.39

Mobility in soil Not established.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F D003: Waste Reactive material The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No.
ERG Code	2X
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable (Hexanes), MARINE POLLUTANT
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.


DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

N-hexane (CAS 110-54-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Skin corrosion or irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

N-hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1, 1 Difluoroethane (CAS 75-37-6)

Pentane (CAS 109-66-0)

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Isopropanol (CAS 67-63-0)

Low priority

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

1, 1 Difluoroethane (CAS 75-37-6)

2-Methylpentane (CAS 107-83-5)

Isopropanol (CAS 67-63-0)

N-hexane (CAS 110-54-3)

Pentane (CAS 109-66-0)

California Proposition 65



WARNING: This product can expose you to N-hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Male reproductive toxin

N-hexane (CAS 110-54-3)

Listed: December 15, 2017

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Isopropanol (CAS 67-63-0)

N-hexane (CAS 110-54-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-27-2016

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information Product and Company Identification: Product and Company Identification
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Transport Information: Material Transportation Information
Regulatory Information: Risk Phrases - Labeling
GHS: Qualifiers