



# QB Precision Duster



## FEATURES

- Non-flammable, odorless, and leaves no residue
- Quick blast precision duster
- Excellent for use on delicate mechanisms and energized electrical equipment
- Moisture free
- Includes with pinpoint extension tube to be used in hard-to-reach spaces
- Removes contaminants, dirt, dust, and other soils
- New Propellant with Lower Global Warming Potential  
<i>Global Warming Potential 100-yr rev. 5 IPCC (GWP CO2 = 1):  
Previous propellant (HFC-134a) = 1300  
New propellant (HFO-1234ze) = <1</i>

## APPLICATIONS

- Avionics
- Computers
- Data Processing Equipment
- Electronic Equipment
- Film Negatives
- Industrial
- Industrial Magnetic Tape Heads
- Laboratory Instruments

## SPECIFICATIONS AND APPROVALS

- Inland Steel
- Kimberly-Clark
- Timken Steel

## PROPERTIES

<b>Appearance / Physical State</b>	Gas
<b>Color</b>	Colorless
<b>Odor</b>	Slight. Ether-like.
<b>Melting / Freezing Point</b>	Not available.
<b>Boiling Point / Range</b>	-2.2 °F (-19 °C)
<b>Flash Point</b>	Not applicable.
<b>Evaporation Rate</b>	Not applicable.
<b>Flammability</b>	Lower Explosive limit (%): None at 20°C; 5.7 % at 60°C Upper Explosive limit (%): None at 20°C; 11.3 % at 60°C
<b>Vapor Pressure</b>	4271 hPa @ 20°C (68°F) 11152 hPa @ 54.4°C (129.9°F)
<b>Vapor Density</b>	4
<b>Density</b>	Not available.
<b>Water Solubility</b>	0.37 g/l @ 25°C
<b>Partition Coefficient</b>	> 1
<b>Auto-Ignition Temperature</b>	694.4°F (368°C)
<b>Viscosity</b>	Not established.
<b>Heat of Combustion</b>	< 20 kJ/g
<b>Percent volatile</b>	100%
<b>Specific Gravity</b>	1.17 @ 21.1°C
<b>VOC Content</b>	0% per State & Federal Consumer Product Regulations
<b>Propellant</b>	HFO-1234ze

## DIRECTIONS

Hold can in upright position. Spray in short bursts until contaminants are removed. Do not tilt, invert or shake can during use. For precision applications, use attached extension tube.

## HANDLING

Avoid breathing vapors. Avoid skin contact with liquid product. Vapors are heavier than air. Keep out of reach of children.

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store aerosols as Level 1 Aerosol (NFPA 30B).

## DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
05710	C05710	12 wt oz / 340 g / 281 mL	aerosol	12	11 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved