

WPB 18 LTX BL 150 (613076860) 6" Cordless Angle Grinder 18V; Cardboard box

Order no. 613076860 EAN 4007430275820



Representative picture















- Versatile cordless angle grinder including two guards for grinding (4-1/2") and cutting (6") applications
- Unique encapsulated Metabo brushless motor with optimum protection from dust provides quick work progress and the highest efficiency for any application
- Slim design for prolonged comfort when working
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Quick braking system for the highest level of User Safety stops the disc in seconds after switching off
- Tool-free adjustable guard; twist-proof
- Battery pack can be swiveled for better working in hard to reach places.
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery replacement
- Detachable dust filter protects motor from coarse particles
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: www.cordless-alliance-system.com

www.metabo.com 1/2



Technical values	
Parameters	
Type of battery pack	Li-Power
Battery voltage	18 V
Disc diameter	6"
No-load speed	9000 RPM
Spindle thread	5/8" - 11 UNC
Weight without battery pack	4.2 lbs
Weight including battery pack	5.5 lbs
Vibration	
Surface grinding	5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	82 dB(A)
Sound power level (LwA)	93 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Clip-on cutting wheel guard 6"

2 guards (4 1/2" and 6")

Inner support flange

Nut with two holes

Side Handle

Dust Protection Filter

Spanner wrench

without battery pack, without charger

www.metabo.com 2/2