


**TOLERANCES**

<i>d1</i>	+0.000" - .001" (+.000 - .025mm)
<i>d2</i>	h6

# HIGH EFFICIENCY MILLING

Series 143M




.1181" - .3150"  
(3.000mm - 8.000mm)

Recommended for aluminum

## HSAL End Mill - Square End ALUMASTAR Coating

- Solid submicron grain carbide end mill - center cutting
- Engineered for High Efficiency Milling
- Specific coating engineered to repel aluminum
- Engineered to run at 750-2500 SFM (225-750 M/Min.)
- For high speed machining of aluminum
- High velocity - high metal removal rate (for 5,000-20,000 RPM spindles)
- Need to use properly balanced holders
- Holds perpendicularity
- Flats can be added within 48 hours



EDP#	<i>d1</i> † Diameter		<i>d2</i> Shank Diameter	<i>l1</i> Overall Length	<i>l2</i> Flute Length	<i>l3</i> Reach Length	<i>d3</i> Neck Diameter
	Decimal	Metric					
41173	.1181	3.000	3.0	38	6	-	-
41183	.1181	3.000	3.0	38	12	-	-
41193	.1250 1/8"	3.175	1/8"	1-1/2"	1/4"	-	-
41203	.1250 1/8"	3.175	1/8"	1-1/2"	1/2"	-	-
41213	.1575	4.000	6.0	50	8	-	-
41223	.1575	4.000	6.0	50	12	-	-
41243	.1575	4.000	6.0	65	6	20	3.7
41273	.1875 3/16"	4.763	3/16"	2"	5/16"	-	-
41283	.1875 3/16"	4.763	3/16"	2"	9/16"	-	-
41303	.1875 3/16"	4.763	3/16"	3"	7/32"	3/4"	.170"
41313	.1875 3/16"	4.763	3/16"	3"	1"	-	-
41343	.1969	5.000	6.0	65	16	-	-
41363	.1969	5.000	6.0	75	8	20	4.7
41403	.2362	6.000	6.0	65	19	-	-
41423	.2362	6.000	6.0	75	10	25	5.7
39735	.2500 1/4"	6.350	1/4"	2"	3/8"	-	-
39737	.2500 1/4"	6.350	1/4"	2"	1/2"	-	-
41453	.2500 1/4"	6.350	1/4"	2-1/2"	3/8"	-	-
41463	.2500 1/4"	6.350	1/4"	2-1/2"	3/4"	-	-
41473	.2500 1/4"	6.350	1/4"	3"	1"	-	-
41475	.2500 1/4"	6.350	1/4"	3"	1-1/4"	-	-
41493	.2500 1/4"	6.350	1/4"	4"	3/8"	1-1/8"	.235"
41503	.2500 1/4"	6.350	1/4"	4"	3/8"	2-1/8"	.235"
41511	.2500 1/4"	6.350	1/4"	4"	1-1/2"	-	-
41513	.2500 1/4"	6.350	1/4"	4"	1-5/8"	-	-
41543	.2756	7.000	8.0	65	19	-	-
41563	.2756	7.000	8.0	75	12	25	6.4
41593	.3125 5/16"	7.938	5/16"	2-1/2"	7/16"	-	-
41603	.3125 5/16"	7.938	5/16"	2-1/2"	3/4"	-	-
41623	.3125 5/16"	7.938	5/16"	4"	7/16"	1-1/8"	.297"
39739	.3150	8.000	8.0	50	12	-	-
41663	.3150	8.000	8.0	65	19	-	-
41683	.3150	8.000	8.0	75	12	25	7.4
41685	.3150	8.000	8.0	75	26	-	-
41687	.3150	8.000	8.0	75	30	-	-
41693	.3150	8.000	8.0	100	12	55	7.4

HIGH PERFORMANCE  
END MILLS

MATERIAL HARDNESS (Rc)  
70  
35  
0

Series 143M (continued)

.3750" - .6299"  
(9.525mm - 16.000mm)

MATERIAL HARDNESS (Rc)

70

35

0

EDP#	$d1$ † Diameter		$d2$ Shank Diameter	$l1$ Overall Length	$l2$ Flute Length	$l3$ Reach Length	$d3$ Neck Diameter	
	Decimal	Metric						
39741	.3750	3/8"	9.525	3/8"	2"	1/2"	-	-
41713	.3750	3/8"	9.525	3/8"	2-1/2"	1/2"	-	-
39743	.3750	3/8"	9.525	3/8"	2-1/2"	3/4"	-	-
41723	.3750	3/8"	9.525	3/8"	2-1/2"	7/8"	-	-
41733	.3750	3/8"	9.525	3/8"	3"	1"	-	-
41735	.3750	3/8"	9.525	3/8"	3"	1-1/4"	-	-
41737	.3750	3/8"	9.525	3/8"	3-1/2"	1-1/2"	-	-
41763	.3750	3/8"	9.525	3/8"	4"	1/2"	2-1/8"	.355"
41773	.3750	3/8"	9.525	3/8"	4"	1-5/8"	-	-
42363	.3750	3/8"	9.525	3/8"	4"	2"	-	-
41783	.3750	3/8"	9.525	3/8"	6"	1/2"	4"	.355"
39745	.3937		10.000	10.0	50	14	-	-
41803	.3937		10.000	10.0	70	24	-	-
41805	.3937		10.000	10.0	75	30	-	-
41843	.3937		10.000	10.0	100	12	35	9.4
41853	.3937		10.000	10.0	100	12	55	9.4
41863	.3937		10.000	10.0	150	12	110	9.4
39747	.4724		12.000	12.0	65	16	-	-
39749	.4724		12.000	12.0	75	26	-	-
41883	.4724		12.000	12.0	75	32	-	-
41893	.4724		12.000	12.0	100	50	-	-
41903	.4724		12.000	12.0	100	16	40	11.4
41913	.4724		12.000	12.0	100	16	55	11.4
41923	.4724		12.000	12.0	150	16	110	11.4
39751	.5000	1/2"	12.700	1/2"	2-1/2"	5/8"	-	-
39753	.5000	1/2"	12.700	1/2"	2-1/2"	3/4"	-	-
41933	.5000	1/2"	12.700	1/2"	3"	5/8"	-	-
39755	.5000	1/2"	12.700	1/2"	3"	1"	-	-
41943	.5000	1/2"	12.700	1/2"	3"	1-1/4"	-	-
41945	.5000	1/2"	12.700	1/2"	3-1/2"	1-1/2"	-	-
41963	.5000	1/2"	12.700	1/2"	4"	1-5/8"	-	-
41965	.5000	1/2"	12.700	1/2"	4"	1-3/4"	-	-
41973	.5000	1/2"	12.700	1/2"	4"	2"	-	-
41983	.5000	1/2"	12.700	1/2"	4"	5/8"	2-1/8"	.475"
41993	.5000	1/2"	12.700	1/2"	6"	5/8"	4-1/8"	.475"
42003	.5000	1/2"	12.700	1/2"	6"	3-1/8"	-	-
39757	.6250	5/8"	15.875	5/8"	3"	3/4"	-	-
42013	.6250	5/8"	15.875	5/8"	3-1/2"	3/4"	-	-
39759	.6250	5/8"	15.875	5/8"	3-1/2"	1"	-	-
42016	.6250	5/8"	15.875	5/8"	3-1/2"	1-1/4"	-	-
42021	.6250	5/8"	15.875	5/8"	4"	1-1/2"	-	-
42023	.6250	5/8"	15.875	5/8"	4"	1-5/8"	-	-
42025	.6250	5/8"	15.875	5/8"	4"	1-3/4"	-	-
42373	.6250	5/8"	15.875	5/8"	4"	2-1/8"	-	-
42033	.6250	5/8"	15.875	5/8"	6"	3/4"	2-3/8"	.590"
42043	.6250	5/8"	15.875	5/8"	6"	3/4"	4-3/8"	.590"
42053	.6250	5/8"	15.875	5/8"	6"	3-1/4"	-	-
42083	.6299		16.000	16.0	100	40	-	-
42103	.6299		16.000	16.0	100	20	40	15.4
42113	.6299		16.000	16.0	125	20	60	15.4
42123	.6299		16.000	16.0	150	20	110	15.4

EDP#	$d1$ † Diameter		$d2$ Shank Diameter	$l1$ Overall Length	$l2$ Flute Length	$l3$ Reach Length	$d3$ Neck Diameter	
	Decimal	Metric						
42133	.7500	3/4"	19.050	3/4"	4"	1"	-	-
42136	.7500	3/4"	19.050	3/4"	4"	1-1/4"	-	-
42141	.7500	3/4"	19.050	3/4"	4"	1-1/2"	-	-
42143	.7500	3/4"	19.050	3/4"	4"	1-5/8"	-	-
42145	.7500	3/4"	19.050	3/4"	4"	1-3/4"	-	-
42153	.7500	3/4"	19.050	3/4"	5"	2-1/4"	-	-
42155	.7500	3/4"	19.050	3/4"	5"	2-1/2"	-	-
42163	.7500	3/4"	19.050	3/4"	6"	1"	2-1/2"	.715"
42173	.7500	3/4"	19.050	3/4"	6"	1"	4-3/8"	.715"
42193	.7500	3/4"	19.050	3/4"	6"	3-1/4"	-	-
42203	.7874		20.000	20.0	100	25	-	-
42213	.7874		20.000	20.0	100	32	-	-
42223	.7874		20.000	20.0	100	20	40	19.0
42226	.7874		20.000	20.0	125	20	60	19.0
42233	.7874		20.000	20.0	150	20	85	19.0
42236	.7874		20.000	20.0	150	20	110	19.0
42243	.9843		25.000	25.0	100	38	-	-
42283	.9843		25.000	25.0	100	25	50	24.0
42286	.9843		25.000	25.0	125	25	65	24.0
42291	.9843		25.000	25.0	150	25	90	24.0
42293	1.000	1"	25.400	1"	4"	1"	-	-
42303	1.000	1"	25.400	1"	4"	1-5/8"	-	-
42313	1.000	1"	25.400	1"	5"	2"	-	-
42343	1.000	1"	25.400	1"	6"	1-1/4"	3-3/8"	.960"
42353	1.000	1"	25.400	1"	6"	3-1/4"	-	-

70

MATERIAL HARDNESS (Rc)

35

0

