



Electro 140° Contact Cleaner



FEATURES

- Superior Wetting and Penetrating Action
- Controlled Evaporation
- Flash Point 140°F (60°C)
- Non-Conductive and Leaves no Residue
- Safe to use on most surfaces
- Inverta Spray Valve

APPLICATIONS

- Coin Counters & Chutes
- Connectors
- Contacts
- Fluid Systems
- Office Equipment
- Relays and Controls
- Semiconductor Assemblies
- Switches
- Telephone Equipment
- Printed Circuits

SPECIFICATIONS AND APPROVALS

- ASTM F-945
- Bombardier (Canadair) BAPS 180-009
- Caterpillar
- Ford Motor Co.
- General Motors Co.
- Kimberly-Clark
- Kodak
- Learjet LES 1239J
- Martin Marietta MMS-M2-10028
- McDonnell Douglas CSD #1 (does not conform to Stress Cracking Test)
- Tampa Electric Co.

PROPERTIES

Appearance / Physical State	Gas
Odor	Mild, Ether-like
Melting / Freezing Point	N/A
Boiling Point / Range	345.2 °F (174 °C)
Vapor Pressure	0.49 mm Hg @ 20°C
Partition Coefficient	<1
Percent volatile	100%
Flammability	lower: 1.2%, upper: 13.1%
Propellant	Carbon Dioxide
VOC Content	96.8%
Color	Colorless
Flash Point	> 140.0 °F (> 60.0 °C) (TCC)
Density	N/A
Evaporation Rate	< 0.1 (BuAc = 1)
Vapor density	5.1 (air = 1)
Auto-Ignition Temperature	> 500 °F (> 260 °C)
Viscosity	N/A
Specific Gravity	0.78 - 0.81 @ 20°C (water=1)
Dielectric Strength	15.14 kV (ASTM D-877)
Surface Tension	25.9 dynes/cm @ 77°F (25°C)

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away from electronic components and spray directly on surface to clean. May attack certain plastics.

HANDLING

Pressurized container: do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.

STORAGE

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, hot surface sparks, open flames, and other ignition sources.

DISPOSAL

Dispose of waste and residues in accordance with local authority requirements.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
00916	C00916	11 wt oz / 312 g / 389 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved