



EVR™

Clean Air Solvent



FEATURES

- No ozone depleting compounds
- Ideal for cleaning metals
- Excellent alternative to Methyl Ethyl Ketone (MEK)
- Instant cleaning action
- High solvent strength
- Fast Evaporating
- Inverta Spray Valve designed to be sprayed at any angle
- Complies with SCAQMD (South Coast Air Quality Management District) Rule 102
- Complies CARB/OTC (California Air Resources Board/Ozone Transport Commission) Rules

APPLICATIONS

- Bearings
- Brakes
- Controls
- Chains
- Cables
- Gauges
- Gears
- Hand & Power Tools
- Heavy Equipment
- De-energized Cable Connectors
- Instruments
- Machinery
- Metal Prep
- Pulleys

SPECIFICATIONS AND APPROVALS

- Airbus ABR 9-0140 Type I
- Boeing D6-17487 Rev. P
- NSF International, C1

PROPERTIES

| | |
|------------------------------------|--|
| Appearance / Physical State | Gas (Aerosol); Liquid (Bulk) |
| Odor | Slight Orange |
| Melting / Freezing Point | Not established |
| Boiling Point / Range | 132.8°F (56°C) |
| Vapor Pressure | Aerosol: 3452mm Hg@20°C; Bulk: 185 mm Hg @20°C |
| Partition Coefficient | Not established |
| Percent volatile | 100% |
| Flammability | Lower (%) 2.5%; Upper (%) 12.8% |
| Propellant | Carbon dioxide |
| VOC Content | 0.5% per US State and Federal Consumer Product Regulations |
| Color | Colorless |
| Flash Point | (-)0.4°F (-18.0°C) Tag Closed Cup |
| Density | Not available |
| Evaporation Rate | 5.6 - 6.1 |
| Vapor density | 2.8 estimated |
| Auto-Ignition Temperature | 582.8°F (306°C) |
| Viscosity | 14 cSt @25°C |
| Specific Gravity | 0.79 @20°C |
| Temperature Range | Not available |
| 4-Ball Weld Load | Not applicable |

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. (see Section 7 of the SDS)

STORAGE

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. (see Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

| Part No. | | Net Contents | Container Type | Units/Case | Case Weight |
|----------|--------|--------------------------|----------------|------------|-------------|
| US | Canada | | | | |
| 05220 | C05220 | 14 wt oz / 397 g/ 492 mL | aerosol | 12 | 15 lbs |
| 05205 | | 5 gal / 18.93 L | pail | 1 | 40 lbs |
| 05255 | C05255 | 55 gal / 208 L | drum | 1 | 369 lbs |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved