SAFETY DATA SHEET



1. Identification

Product identifier LPS® Precision Clean (Aerosol)

Other means of identification

Part Number 02720

Recommended use An industrial cleaner designed to remove grime, oils and light grease from metal, concrete and

other durable surfaces.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company name ITW Pro Brands **Address** 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.itwprobrands.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazardsGases under pressureLiquefied gasHealth hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye

irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: LPS® Precision Clean (Aerosol)

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum Gases, Liquefied, Sweetened		68476-86-8	1 - 5

02720 Version #: 03 Revision date: 11-30-2022 Issue date: 11-01-2016

Chemical name	Common name and synonyms	CAS number	%
Silicic acid, Disodium salt		6834-92-0	1 - 3
Other components below reportable levels			94.02

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or

Not likely, due to the form of the product. In the unlike

poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

Ingestion

media

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media
Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Cool containers exposed to flames with water until well after the fire is out.

General fire hazards Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

SDS US

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Form Aerosol. Liquefied gas.

Color Clear Blue Odor Citrus.

Odor threshold Not available.

12.7 pН

Not available. Melting point/freezing point Initial boiling point and boiling 200 °F (93.33 °C)

range

Flash point Not Established

Evaporation rate 1 BuAc

Non flammable gas. Flammability (solid, gas)

Upper/lower flammability or explosive limits Explosive limit - lower (%) Not Established

Explosive limit - upper (%) Not Established Vapor pressure < 17.5 mm Hg @20°C

Material name: LPS® Precision Clean (Aerosol) 02720 Version #: 03 Revision date: 11-30-2022 Issue date: 11-01-2016

Not available. Vapor density Relative density Not available.

Solubility(ies)

100 % (in water) Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Viscosity < 3 cSt

Viscosity temperature 77 °F (25 °C)

Other information

1.02 g/cm3 Density Not explosive. **Explosive properties** Heat of combustion < 20 kJ/g Oxidizing properties Not oxidizing.

Specific gravity 1.04

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat. Contact with incompatible materials. Do not mix with other chemicals.

Incompatible materials Acids. Oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Skin contact Causes skin irritation. Eye contact Causes eye irritation.

Ingestion May cause discomfort if swallowed. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Causes eye irritation. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Exposure may cause

temporary irritation, redness, or discomfort.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic. Not expected to be acutely toxic.

Test Results Components **Species**

Silicic acid, Disodium salt (CAS 6834-92-0)

Acute Dermal

LD50 Rat > 5000 mg/kg, 24 Hours

Skin corrosion/irritation Causes skin irritation.

Causes serious eye irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not likely, due to the form of the product. Not classified.

Aspiration hazard Chronic effects

Prolonged or repeated contact may cause drying, cracking, or irritation.

Further information None known.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

Expected to biodegrade.

Mobility in soil Not established. Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

D003: Waste Reactive material

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Transport hazard class(es) AEROSOLS, non-flammable

Class 2.2

Subsidiary risk 2.2 Label(s)

Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1950

UN proper shipping name

Transport hazard class(es)

AEROSOLS, non-flammable

Class 2.2

Subsidiary risk 2.2 Label(s)

Not available. Packing group

Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

02720 Version #: 03 Revision date: 11-30-2022 Issue date: 11-01-2016

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Transport hazard class(es) AEROSOLS, non-flammable

Class 2.2 Subsidiary risk -Label(s) 2.2

Packing group

Not available.

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety ins nsport in bulk according to Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

All components of the mixture on the TSCA 8(b) inventory are designated

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

"active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Toxic Substances Control Act (TSCA)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Gas under pressure Skin corrosion or irritation categories

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs. tit. 22, 69502.3, subd.

Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)

California Proposition 65



WARNING: This product can expose you to 2-methoxyethanol, which is known to the State of California to

cause birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Developmental toxin

2-methoxyethanol (CAS 109-86-4) Listed: January 1, 1989

California Proposition 65 - CRT: Listed date/Male reproductive toxin

2-methoxyethanol (CAS 109-86-4) Listed: January 1, 1989

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Europe European List of Notified Chemical Substances (ELINCS) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

11-01-2016 Issue date **Revision date** 11-30-2022

03 Version #

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text, ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: LPS® Precision Clean (Aerosol)

SDS US

02720 Version #: 03 Revision date: 11-30-2022 Issue date: 11-01-2016

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing