

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Issue date: 06/09/2017

Revision date: 01/20/2021

Supersedes: 09/04/2020

Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini
 Synonyms : Quik Stik®+ Oily Surface-Mini - White, Yellow, Red, Black, Blue, Green, Fluorescent Yellow / Quik Stik®+ Oily Surface - White, Yellow, Red, Black

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Marking.
 Restrictions on use : No data available

1.3. Supplier

LA-CO Industries, Inc.
 1201 Pratt Boulevard
 Elk Grove Village, IL. 60007-5746
 Phone: (847) 956-7600
 Fax: (847) 956-9885
 E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887;
 全国应急中心 0532 8388 9090

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Skin corrosion/irritation, Category 2 H315 Causes skin irritation.
 Serious eye damage/eye irritation, Category 1 H318 Causes serious eye damage.
 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412 Harmful to aquatic life with long lasting effects.
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

H315 - Causes skin irritation.
 H318 - Causes serious eye damage.
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS) :

P264 - Wash hands thoroughly after handling.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, eye protection.
 P302+P352 - If on skin: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a doctor.
 P321 - Specific treatment (see First aid measures on this label).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No data available

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

2.4. Unknown acute toxicity (GHS)

63.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

63.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

63.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Titanium dioxide	(CAS-No.) 13463-67-7	5 - 20	Carc. 2, H351
Stearmide MEA	(CAS-No.) 111-57-9	5 - 15	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Carbon black	(CAS-No.) 1333-86-4	0 - 10	Carc. 2, H351
Methyl ester, soybean oil	(CAS-No.) 68919-53-9	1 - 7	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS-No.) 2786-76-7	0 - 7	Skin Sens. 1, H317
ethyl lactate	(CAS-No.) 97-64-3	1 - 5	Flam. Liq. 3, H226 Eye Dam. 1, H318 STOT SE 3, H335
Ethyl acetate	(CAS-No.) 141-78-6	0.1 - 2	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Butyl acetate	(CAS-No.) 123-86-4	0.5 - 2	Flam. Liq. 3, H226 STOT SE 3, H336

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash skin with mild soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye damage.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Protection during firefighting : chemical fire. Prevent fire fighting water from entering the environment.
: Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothing. Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain and collect as any solid.

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimise generation of dust. Store away from other materials.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep only in the original container.

Incompatible products : Strong oxidizers.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethyl lactate (97-64-3)		
Not applicable		
Ethyl acetate (141-78-6)		
ACGIH	Local name	Ethyl acetate
ACGIH	ACGIH TWA (mg/m ³)	1440 mg/m ³
ACGIH	ACGIH OEL TWA [ppm]	400 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL TWA [1]	1400 mg/m ³
OSHA	OSHA PEL TWA [2]	400 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL TWA	1400 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	400 ppm

Quik Stik ®+ Oily Surface, Quik Stik ®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Methyl ester, soybean oil (68919-53-9)		
Not applicable		
Butyl acetate (123-86-4)		
ACGIH	Local name	n-Butyl acetate
ACGIH	ACGIH TWA (mg/m ³)	713 mg/m ³
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH STEL (mg/m ³)	950 mg/m ³
ACGIH	ACGIH OEL STEL [ppm]	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL TWA [1]	710 mg/m ³
OSHA	OSHA PEL TWA [2]	150 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL TWA	710 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	150 ppm
NIOSH	NIOSH REL STEL	950 mg/m ³
NIOSH	NIOSH REL STEL [ppm]	200 ppm
Stearmide MEA (111-57-9)		
Not applicable		
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)		
Not applicable		
Titanium dioxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL TWA [1]	15 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (I - Inhalable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL TWA [1]	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL TWA	3.5 mg/m ³
NIOSH	NIOSH REL STEL	0.1 mg/m ³

8.2. Appropriate engineering controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.
- Environmental exposure controls : Prevent leakage or spillage.

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

None under normal use

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable
Odour	: odourless
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Unknown acute toxicity (GHS)	63.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 63.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 63.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
------------------------------	--

ethyl lactate (97-64-3)	
LD50 oral rat	> 4090 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5400 mg/m ³

Ethyl acetate (141-78-6)	
LD50 oral rat	4934 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 Inhalation - Rat	> 18 mg/l/4h
ATE (oral)	4934 mg/kg bodyweight

Butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 Inhalation - Rat	> 21 mg/l/4h
ATE (oral)	10760 mg/kg bodyweight

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LD50 oral rat	> 15000 mg/kg
LC50 Inhalation - Rat	> 1580 mg/m ³ 4 h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 6.82 mg/l/4h

Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 Inhalation - Rat	> 4.6 mg/m ³ 4 h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : Not classified. (4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) not sensitizing <10%)

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

Titanium dioxide (13463-67-7)	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
Additional information	Carcinogen, cat 1A or 1B Inhalation of dust
IARC group	2B - Possibly carcinogenic to humans

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
ethyl lactate (97-64-3)	
STOT-single exposure	May cause respiratory irritation.
Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
Butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Ethyl acetate (141-78-6)	
NOAEL (subchronic, oral, animal/male, 90 days)	900 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	900 mg/kg bodyweight
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Skin and eye contact.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

Ethyl acetate (141-78-6)	
LC50 fish 1	220 mg/l
EC50 crustacea	1200 mg/l
NOEC chronic fish	> 75.6 mg/l 32 d
Stearmide MEA (111-57-9)	
LC50 fish 1	31 mg/l 96 h read-across
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LC50 fish 1	> 500 mg/l 96 h
EC50 crustacea	> 110 mg/l 48 h

12.2. Persistence and degradability

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini	
Persistence and degradability	May cause long-term adverse effects in the environment.
ethyl lactate (97-64-3)	
Persistence and degradability	Readily biodegradable.
Ethyl acetate (141-78-6)	
Persistence and degradability	Readily biodegradable.
Stearmide MEA (111-57-9)	
Biodegradation	69 % 28 d
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

Quik Stik ®+ Oily Surface, Quik Stik ®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Quik Stik ®+ Oily Surface, Quik Stik ®+ Oily Surface-Mini	
Bioaccumulative potential	Not established.

Ethyl acetate (141-78-6)	
Bioaccumulative potential	Not expected to bioaccumulate.

Stearmide MEA (111-57-9)	
Log Pow	> 4.46

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28

12.4. Mobility in soil

Quik Stik ®+ Oily Surface, Quik Stik ®+ Oily Surface-Mini	
Ecology - soil	Not established.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Other information :No supplementary information available

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Ethyl acetate (141-78-6)	
CERCLA RQ	5000 lb

Butyl acetate (123-86-4)	
CERCLA RQ	5000 lb

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

15.2. International regulations

CANADA

No data available

Ethyl acetate (141-78-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Methyl ester, soybean oil (68919-53-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Stearmid MEA (111-57-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

National regulations

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

All ingredients are listed in the Domestic Substances List (DSL).

Ethyl acetate (141-78-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Chinese Catalog of Hazardous Chemicals.
Listed on Chinese List of Hazardous Chemicals for Priority Management-SAWS
Listed on the China threshold of permit for use of hazardous chemicals
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on the Korea Designated Existing Substances List (First Batch).
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Titanium dioxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Carbon black (1333-86-4)

Listed on Taiwan National Chemical Inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
Listed on the Japanese ISHL (Industrial Safety and Health Law)

15.3. US State regulations

Fluorescent Yellow

Quik Stik®+ Oily Surface-Mini Fluorescent Yellow

State or local regulations	The titanium dioxide in this product is bound and is not respirable.
----------------------------	--

⚠ WARNING: This product can expose you to formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
formaldehyde(50-00-0)	X				40 µg/day	
Titanium dioxide(13463-67-7)	X					

Component	State or local regulations
ethyl lactate(97-64-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
Ethyl acetate(141-78-6)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List
Butyl acetate(123-86-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide(13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

White, Yellow, Red, Black, Blue, Green

Quik Stik®+ Oily Surface, Quik Stik®+ Oily Surface-Mini

State or local regulations	The Carbon black in this product is bound and is not respirable. The titanium dioxide in this product is bound and is not respirable. California Prop. 65 warnings are not required.
----------------------------	--

Component	State or local regulations
ethyl lactate(97-64-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
Ethyl acetate(141-78-6)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List
Butyl acetate(123-86-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide(13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Quik Stik ®+ Oily Surface, Quik Stik ®+ Oily Surface-Mini

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Revision date	: 01/20/2021
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Other information	: None.


Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:
Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.