

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Date of issue: 10/07/2015

Revision date: 09/10/2019

Supersedes: 05/20/2019

Version: 5.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Security Check Paint Marker
 Synonyms : Security Check Paint Marker - Black, Blue, Green, Red, White, Yellow, Orange, Purple

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Marking.
 Restrictions on use : No additional information available

1.3. Supplier

LA-CO Industries, Inc.
 1201 Pratt Boulevard
 Elk Grove Village, IL. 60007-5746
 Phone: (847) 956-7600
 Fax: (847) 956-9885
 E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887;
 全国应急中心 0532 8388 9090

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flammable liquids, Category 3 H226 Flammable liquid and vapour.
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 May cause drowsiness or dizziness.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Warning
 Hazard statements (GHS) : H226 - Flammable liquid and vapour.
 H336 - May cause drowsiness or dizziness.
 Precautionary statements (GHS) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P312 - Call a poison center/doctor if you feel unwell
 P370+P378 - In case of fire: Use media other than water to extinguish.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 - Store in a well-ventilated place. Keep cool.

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS_US)

1.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
1.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
1.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Butyl acetate	(CAS-No.) 123-86-4	25 - 55	Flam. Liq. 3, H226 STOT SE 3, H336
Titanium dioxide	(CAS-No.) 13463-67-7	0 - 7	Carc. 2, H351
Silicon dioxide (cristobalite)	(CAS-No.) 14808-60-7	0.5 - 1.5	Carc. 1A, H350
Carbon black	(CAS-No.) 1333-86-4	0 - 1	Carc. 2, H351

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
First-aid measures after ingestion : Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause drowsiness or dizziness. Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour. Burning produces irritating, toxic and noxious fumes.
Explosion hazard : May form flammable/explosive vapour-air mixture.
Reactivity : No dangerous reactions known.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flammable resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

6.1.1. For non-emergency personnel

Protective equipment : Large amounts: Wear suitable protective clothing and gloves. Chemical goggles or safety glasses.
Emergency procedures : Evacuate area.

6.1.2. For emergency responders

Protective equipment : Large amounts: Wear suitable protective clothing and gloves, Chemical goggles or safety glasses.
Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Do not allow minor leaks or spills to accumulate on walking surfaces.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container. Following recovery, flush area with water. Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. Use only outdoors or in a well-ventilated area.
Hygiene measures : Always wash your hands immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.
Incompatible products : Strong acids. Strong bases. Strong oxidizers.
Incompatible materials : Heat sources. Direct sunlight.
Heat and ignition sources : Keep away from heat, sparks and flame.
Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in dry, cool, well-ventilated area. Keep out of direct sunlight. Keep out of reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butyl acetate (123-86-4)		
ACGIH	Local name	n-Butyl acetate
ACGIH	ACGIH TWA (mg/m ³)	713 mg/m ³
ACGIH	ACGIH TWA (ppm)	150 ppm
ACGIH	ACGIH STEL (mg/m ³)	950 mg/m ³
ACGIH	ACGIH STEL (ppm)	200 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	710 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	950 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	200 ppm

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³
ACGIH	Remark (ACGIH)	Bronchitis
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³
NIOSH	NIOSH REL (STEL) (mg/m ³)	0.1 mg/m ³
Titanium dioxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Silicon dioxide (cristobalite) (14808-60-7)		
ACGIH	Local name	Silica crystalline - quartz
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (R - Respirable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (ppm)	250 mppcf
OSHA	Remark (OSHA)	(3) See Table Z-3.
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
NIOSH	Remark (NIOSH)	(respirable dust)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

None under normal use.

Eye protection:

None under normal use

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Wear appropriate mask.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Solid marker containing liquid colored paint.
Colour : Variable

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: 21 - 55 °C
Boiling point	: > 35 °C
Flash point	: 27.5 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: < 110 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: Lower explosive limit (LEL): 1.2 vol % Upper explosive limit (UEL): 7.5 vol %
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content : ≈ 50 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

Strong bases. Strong oxidizers. Strong acids.

10.6. Hazardous decomposition products

May release flammable gases. Burning produces irritating, toxic and noxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Unknown acute toxicity (GHS_US)	1.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 1.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 1.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
---------------------------------	---

Butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Butyl acetate (123-86-4)	
LC50 inhalation rat (mg/l)	> 21 mg/l/4h
ATE (oral)	10760 mg/kg bodyweight

Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust

Titanium dioxide (13463-67-7)	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
Additional information	Carcinogen, cat 1A or 1B Inhalation of dust
IARC group	2B - Possibly carcinogenic to humans

Silicon dioxide (cristobalite) (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

Butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Likely routes of exposure : Inhalation. Skin and eye contact.
Symptoms/effects after inhalation : May cause drowsiness or dizziness. Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecotoxicological data about this product are known.

12.2. Persistence and degradability

Security Check Paint Marker	
Persistence and degradability	Not established.

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Security Check Paint Marker	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Security Check Paint Marker	
Ecology - soil	No additional information available.

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

12.5. Other adverse effects

Other information : No additional information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN1263 Paint, 3, III
UN-No. (TDG) : UN1263
Proper Shipping Name (Transportation of Dangerous Goods) : Paint
Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Packing group : III - Minor Danger

Transport by sea

Transport regulations (IMDG) : Transport in accordance with section 2.3.2.5 of the IMDG (viscous substance) may be applied
Transport document description (IMDG) : UN 1263 PAINT, 3, III
UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 1263 PAINT, 3, III
UN-No. (IATA) : 1263
Proper Shipping Name (IATA) : PAINT
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum oxide	CAS-No. 1344-28-1	< 0.1%
----------------	-------------------	--------

Butyl acetate (123-86-4)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

Security Check Paint Marker

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS). All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

Security Check Paint Marker

State or local regulations	The Carbon black in this product is bound and is not respirable. The titanium dioxide in this product is bound and is not respirable. This product is not expected to produce Silicon dioxide particles of respirable size. California Prop. 65 warnings are not required.
----------------------------	---

Component	State or local regulations
Butyl acetate(123-86-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide(13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List
Silicon dioxide (cristobalite)(14808-60-7)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 09/10/2019
Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
Other information : None.

Full text of H-statements:

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.

Security Check Paint Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

H351	Suspected of causing cancer.
------	------------------------------

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Transport information.

SDS Prepared by: The Redstone Group
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43017
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.