



www.wearwell.com

UltraSoft Diamond-Plate SpongeCote - Gray Anti Fatigue Mats

Group 414GY



Outperforms other Diamond-Plate workstation mats in the market. Wearwell's Diamond-Plate SpongeCote mats have a unique Nitricell sponge base that delivers twice the resilience and three times the life expectancy of simple PVC sponge anti-fatigue mats. Pre-beveled edge assures a perfect lays flat quality, and the bevel extends the sponge within 1.5 inches of the mat's surface for 20% more standing area than other anti-fatigue mats.

Designed for comfort and optimized worker productivity, these ergonomic mats are exceedingly popular among standing workers and have industrial strength for multiple shift operations. The double-thick Nitricell sponge base is a Nitrile composite for exceptional comfort, rebound, and long life. Ideal for high traffic areas in heavy manufacturing and in high traffic fulfillment operations.

- NFSI Certified
- Wearwell Nitricell sponge base
- Tough abrasion and chemical resistant PVC surface
- Diamond-Plate pattern for improved traction
- Machine cut, pre-beveled edges prevent tripping
- Overall thickness 15/16"
- Chemical and abrasion resistant
- 2X the resilience and 3X the life of other anti-fatigue mats
- Maximized standing area
- Ultra 15/16in thickness
- Also available in black, black w/ yellow borders and black w/ chevron borders
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Type	Anti-Fatigue Matting
Suitable Environment	Dry
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC Surface With Nitrile Infused Sponge
Recycled	>50%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191
Temperature Range	Not Available
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=13.20

Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
414.1516x2x3GY	715411261390	Gray	0.9375	2' x 3'	Y	EA
414.1516x2x75GY	715411261666	Gray	0.9375	2' x 75'	Y	RL
414.1516x3x10GY	715411262212	Gray	0.9375	3' x 10'	N	EA
414.1516x3x5GY	715411262205	Gray	0.9375	3' x 5'	Y	EA