



www.wearwell.com

Diamond-Plate SpongeCote Mat - Gray Anti Fatigue Mats

Group 415GY



Designed for comfort and optimized worker productivity, these ergonomic floor mats are exceedingly popular among standing workers and workers in motion. Made for industrial strength and easily stands up to multiple shift operations. Ideal for high traffic areas in any manufacturing setting. A popular choice for high traffic fulfillment operations.

Diamond-Plate Premium **Anti-fatigue Workstation Mats outperform compared to off-brand floor mats** in the market. The unique Nitricell sponge base of this floor mat delivers twice the resilience and three times the life expectancy of simple PVC sponge anti-fatigue mats. Nitricell is a Nitrile composite that provides exceptional comfort, rebound, and long life. The safety bevel extends the sponge within 3 inches of the mat's surface for more ergonomic standing area. Great news for standing workers.

- National Floor Safety Institute Certified
- Proprietary Nitricell sponge base
- Floor mat features a tough abrasion and chemical resistant PVC surface
- Diamond-plate pattern provides improved traction
- Sizes for workstations and runners
- Made in USA
- Lay-flat design helps prevent tripping
- Overall thickness 9/16"
- Chemical and abrasion resistant
- 2X the resilience and 3X the life compared to off-brand anti-fatigue floor mats
- Maximized standing area for optimal ergonomic performance
- Anti-fatigue floor mats are proven to reduce injuries in the workplace
- The use of anti-fatigue flooring is documented to support an overall increase in worker productivity
- Also available in black, black w/ yellow borders and black w/ chevron borders
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Type	Anti-Fatigue Matting
Suitable Environment	Dry
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC Surface With Nitrile Infused Sponge
Recycled	>50%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel

Temperature Range	-10 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=8.43
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
415.916x2x3GY	715411200764	Gray	0.5625	2' x 3'	Y	EA
415.916x2x75GY	715411200740	Gray	0.5625	2' x 75'	N	RL
415.916x3x10GY	715411200863	Gray	0.5625	3' x 10'	N	EA
415.916x3x5GY	715411200979	Gray	0.5625	3' x 5'	Y	EA
415.916x3x75GY	715411200962	Gray	0.5625	3' x 75'	N	RL
415.916x4x75GY	715411201075	Gray	0.5625	4' x 75'	N	RL