



www.wearwell.com

UltraSoft Tile-Top AM - Black Anti Fatigue Mats

Group 419BK



If you work on your feet all day, UltraSoft Tile-Top floor matting is the choice for champions like you. These floor mats are **ultra-comfortable and provide best-in-class anti-fatigue and ergonomic support**. Featuring top-of-the-line AM Nitricell Sponge with supreme resilience over its entire lifetime.

UltraSoft Tile Top Anti-fatigue floor mats are the perfect choice for medical, kitchen, lab, pharmacy and healthcare applications because of its **anti-microbial characteristics** that inhibit the growth of organic compounds and bacteria, keeping your standing area more hygienic. Popular marble top (marbleized) style floor mats are available in dozens of sizes and four colors.

- Best Nitricell Sponge for extended performance of anti-fatigue mats
- 2X the resilience and 3X product life of look-alike floor mats
- 20% more standing area
- Wearwell brand Lay-flat design - Built-in trip prevention with beveled safety edges
- Perfect mat for workstations and standing height desks
- Available in multiple colors & sizes
- 7/8" thick for maximum comfort and ergonomic support
- Meets the ASTM G21 standard for anti-microbial properties
- Non-porous, Anti-Microbial surface - 100% AM
- Premium Anti-Microbial sponge layer
- NFSI Certified (National Floor Safety Institute)
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about Tile-Top ergonomic matting [here](#).

Type Anti-Fatigue Matting

Suitable Environment Dry

Customization Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC Surface With Anti-Microbial Nitrile Infused Sponge

Recycled <10%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	ASTM D395-98 / 20%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMBK	715411031962	Black	0.875	2' x 3'	Y	EA
419.78x2X60AMBK	715411029105	Black	0.875	2' x 60'	Y	RL
419.78x3X10AMBK	715411328000	Black	0.875	3' x 10'	N	EA
419.78x3X5AMBK	715411032594	Black	0.875	3' x 5'	Y	EA
419.78x3X60AMBK	715411029853	Black	0.875	3' x 60'	Y	RL
419.78x4X60AMBK		Black	0.875	4' x 60'	Y	RL