



www.wearwell.com

UltraSoft Tile-Top AM - Blue Anti Fatigue Mats

Group 419BL



If you work on your feet all day, UltraSoft Tile-Top floor matting is the choice for you. These high quality floor mats are ultra-comfortable and provide **best-in-class anti-fatigue and ergonomic support**. Featuring top-of-the-line AM Nitricell Sponge with supreme resilience over its entire lifetime.

Perfect choice for medical, kitchen, lab applications because of its **anti-microbial characteristics** that inhibit the growth of organic compounds and bacteria, keeping your standing area more hygienic. Popular marble top (marbleized) style floor mats are available in dozens of sizes and four colors.

- Lay-flat design - Built-in trip prevention with beveled safety edges
- NFSI (National Floor Safety Institute) Certified
- Perfect mat for healthcare workstations and standing height desks
- Best Nitricell Sponge for extended performance of anti-fatigue mats
- 2X the resilience and 3X product life of look-alike floor mats
- 20% more standing area
- 7/8" thick for Maximum comfort and ergonomic properties
- Anti Microbial (AM) surface delivers added abrasion and chemical resistance.
- Meets the ASTM G21 standard for anti-microbial properties
- Non-porous, Anti-Microbial surface - 100% AM
- Premium Anti-Microbial sponge layer
- Available in multiple colors & sizes
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about Tile-Top ergonomic matting [here](#).

Type Anti-Fatigue Matting

Suitable Environment Dry

Customization Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC Surface With Anti-Microbial Nitrile Infused Sponge

Recycled <10%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	ASTM D395-98 / 20%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMBL	715411029709	Blue	0.875	2' x 3'	Y	EA
419.78x2X60AMBL	715411030668	Blue	0.875	2' x 60'	Y	RL
419.78x3X10AMBL	715411328109	Blue	0.875	3' x 10'	N	EA
419.78x3X5AMBL	715411032600	Blue	0.875	3' x 5'	Y	EA
419.78x3X60AMBL	715411030064	Blue	0.875	3' x 60'	Y	RL
419.78x4X60AMBL		Blue	0.875	4' x 60'	Y	RL