



www.wearwell.com

## UltraSoft Tile-Top AM - Charcoal Anti Fatigue Mats

Group 419CH



If you work on your feet all day, UltraSoft Tile-Top floor matting is the choice for champions like you. These floor mats are **ultra-comfortable and provide best-in-class anti-fatigue and ergonomic support**. Featuring top-of-the-line AM Nitricell Sponge with supreme resilience over its entire lifetime.

UltraSoft Tile Top Anti-fatigue floor mats are the perfect choice for medical, kitchen, lab, pharmacy and healthcare applications because of its **anti-microbial characteristics** that inhibit the growth of organic compounds and bacteria, keeping your standing area more hygienic. Popular marble top (marbleized) style floor mats are available in dozens of sizes and four colors.

- Features Best Nitricell Sponge for extended performance of anti-fatigue mats

- 2X the resilience and 3X product life of look-alike floor mats
- Wearwell brand Lay-flat design - Built-in trip prevention with beveled safety edges

- Works for workstations and standing height desks
- Available in multiple colors & sizes
- 20% more standing area
- 7/8" thick for Maximum comfort and ergonomic support
- Meets the ASTM G21 standard for anti-microbial properties
- Non-porous, Anti-Microbial surface - 100% AM
- Premium anti-microbial sponge layer
- NFSI Certified
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about Tile-Top ergonomic matting [here](#).

**Type** Anti-Fatigue Matting

**Suitable Environment** Dry

**Customization Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** PVC Surface With Anti-Microbial Nitrile Infused Sponge

**Recycled** <10%

**Warranty** Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	ASTM D395-98 / 20%
Tear Strength	Not Available

ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMCH	715411033256	Charcoal	0.875	2' x 3'	Y	EA
419.78x2X60AMCH	715411031689	Charcoal	0.875	2' x 60'	Y	RL
419.78x3X10AMCH	715411106578	Charcoal	0.875	3' x 10'	N	EA
419.78x3X5AMCH	715411032686	Charcoal	0.875	3' x 5'	Y	EA
419.78x3X60AMCH	715411031757	Charcoal	0.875	3' x 60'	Y	RL
419.78x4X60AMCH	715411029181	Charcoal	0.875	4' x 60'	Y	RL