



www.wearwell.com

ErgoDeck Comfort Solid

Group 556

ErgoDeck Comfort Solid provides “rubber-like” resilience underfoot with its spring-back design...engineered to cushion the impact of long-term standing. It is especially suited to work areas that remain relatively dry, or have slight overspray. The raised surface design delivers substantial traction. U.S. Patent No. D681,993

- Customize in 3" increments to fit any area or configuration
- [LockSafe](#) Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in solid for standing relief in dry applications
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Learn more about the benefits of ErgoDeck in our blog - [Top 6 Benefits of ErgoDeck Anti-Fatigue Floors](#).

Type	Anti-Fatigue Flooring
Suitable Environment	Dry, Wet
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Compound	PVC
Recycled	>80%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .65 / Wet: COF = .42
Compression Deflection	ASTM D575-91 / 14.15%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
556.78x18x18CH-CS10	715411013241	Charcoal	0.875	18" x 18"	Y	CS-10