WEARWELL[®]



www.wearwell.com

24/Seven LockSafe Nitrile Rubber (NBR) - Male Edging, Yellow

Group 578-MNBRYL

24/Seven LockSafe Nitrile Rubber (NBR) male edging securely interlocks with 24/Seven LockSafe NBR modular tiles. NBR is suitable for more demanding areas that require optimum chemical resistance. Yellow edging acts as a visual cue and provides a smooth transition for foot traffic.

- Nitrile Rubber (NBR)
- Ideal for dry areas or areas with water
- 3" wide
- Overall thickness 5/8"
- Corners and female edging available
- Available in black and yellow

Туре	Anti-Fatigue Flooring
Suitable Environment	Dry, Wet, Oily, Slippery
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	Nitrile Rubber (NBR)
Recycled	>50%
Warranty	1 Year

Property				Test / Result				
Flammability			MVSS 3	MVSS 302 / 'A'; Rating				
Taber Abrasion			Federa	Federal Standard 191 Modified / 1% loss				
Temperature Range			10 to 1	10 to 140 F				
Coefficient of Friction			ASTM F	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94				
Compression Deflection			Not Ap	Not Applicable				
Tear Strength			Not Ap	Not Applicable				
ESD Rating			Not Ap	Not Applicable				
Dielectric Strength			Not Ap	Not Applicable				
SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM		